


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	7/8/2016	RJC	JAG




NOTE:
REF. AGUSTA T/N: 109-3130-51-101.

DART AEROSPACE	
TITLE TAIL ROTOR BRAKE NUT REMOVAL / INSTALLATION TOOL	
DWG NO. RBW109-3130-51-101	REV 1
MAT'L REAT TREAT FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125°
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: DUERFELDT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: ANDERSON	USED ON MODEL
QA APPR: LINDSAY	AW109
APPROVED: GILBERT	
SCALE 1:2	DATE 7/24/2013
SHEET 1 OF 3	




ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	KEY, LOCKING	4140/4142 Q & T		2
			-3	1	WRENCH CENTERING	4140/4142 Q & T		3

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



SECTION A-A




(-1)

KEY, LOCKING


DART AEROSPACE	
TITLE TAIL ROTOR BRAKE NUT REMOVAL / INSTALLATION TOOL	
DWG NO. RBW109-3130-51-101-1	REV 1
MAT'L 4140/4142 Q & T HEAT TREAT FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2 DRAWN BY: CLOUGH CHECKED: DUERFELDT OPPTS APPR: ANDERSON QA APPR: LINDSAY APPROVED: GILBERT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125✓ 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
USED ON MODEL AW109	
SCALE 1:2	DATE 7/24/2013
SHEET 2 OF 3	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS			
REV	ECR	DESCRIPTION	DATE INITIAL APPROVED



SECTION B-B



WRENCH CENTERING



INTERNAL SPLINE DATA	
STANDARD	ANSI B92.1-1996
ROOT & FIT	FILLET ROOT SIDE FIT
NUMBER OF TEETH	24
DIAMETRAL PITCH	20/40
PRESSURE ANGLE	30°
MAJOR DIAMETER	1.2900 - 1.3049
MINOR DIAMETER	1.1500 - 1.2540
DIA. OVER Ø.0864 PINS	Ø1.0778 - 1.0803
TOLERANCE CLASS	CLASS 5 FIT

DART AEROSPACE	
TITLE TAIL ROTOR BRAKE NUT REMOVAL / INSTALLATION TOOL	
DWG NO. RBW109-3130-51-101-3	REV 1
MAT'L 4140/4142 Q & T HEAT TREAT FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2 DRAWN BY: CLOUGH CHECKED: DUERFELDT OPPTS APPR: ANDERSON QA APPR: LINDSAY APPROVED: GILBERT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125° 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
USED ON MODEL AW109	
SCALE 1:1	DATE 7/24/2013
SHEET 3 OF 3	